cAP lite


The cAP lite is a tiny access point device with a clean and simple design which will blend into any environment. Perfect for public locations and hospitality businesses like hotels, airports, shopping malls etc. where you can easily place it out of sight, or customise it's looks, to make it even less conspicuous.





Included with the product are two different casings, which can easily be swapped out, or, if you really like to fit the design with the environment, we are providing 3D printer friendly design files. The customisation possibilities are endless.

The cAP lite supports 802.11b/g/n and can be powered by power over ethernet. It's a perfect companion for the MikroTik CAPsMAN (controlled AP system manager), allowing you to control all your AP devices from one central location. The cAP lite can also be used as a stand alone access point with the full potential of RouterOS.



cAP lite



Specifications

Product code	cAP lite	
CPU	QCA9533	
CPU nominal frequency	650 MHz	
CPU core count	1	
Size of RAM	64 MB	
10/100 Ethernet ports	1	
Wireless	Built-in 2.4 GHz 802.11b/g/n, dual-chain	
Antenna gain	1.5 dBi	
Antenna beam width	360°	
Wireless chip model	QCA9531	
PoE in	Yes	
Supported input voltage	5 V - 60 V (jack, 802.3af/at or passive PoE)	
Operating temperature	-40°C +70°C tested	
Dimensions	Wall case: 88 x 52 x 20 mm Ceiling case: Ø88 mm x 20 mm	
License level	4	
Operating System	RouterOS	
Max Power consumption	4 W	

Wireless specifications

RATE	Tx (dBm)	Rx (dBm)
1MBit/s	22	-96
11MBit/s	22	-89
6MBit/s	20	-93
54MBit/s	18	-74
MCS0	20	-93
MCS7	16	-71

Included



24 V 0.2 A power adapter



Fastening set



PoE injector



Ceiling case





Custom case 3D model file and instructions are provided on routerboard.com.

cAP lite



Small and in different shapes



